Revision Date 03/14/2024 Print Date 03/16/2024

## SECTION 1. IDENTIFICATION

Todal Products Company name

25 Washington Ave

USA Natick, MA 01760

PO BOX 398

Telephone : 1-800-252-3818

Telefax : 508-651-0729

E-mail address : info@todol.com

Emergency telephone : 24/7 USA: 800-535-5053

24/7 Global: 352-323-3500

Recommended use of the

chemical and restrictions on

use

For further information, refer to product data sheet.

#### SECTION 2. HAZARDS IDENTIFICATION

## GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1

Gases under pressure Compressed gas

Eye irritation Category 2A

single exposure

Specific target organ toxicity : Category 3 (Central nervous system)

### GHS label elements

Hazard pictograms







Signal Word Danger

Hazard Statements H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary Statements P101 If medical advice is needed, have product container or la-

bel at hand.

P102 Keep out of reach of children. P103 Read label before use.

Revision Date 03/14/2024

Print Date 03/16/2024

### Prevention:

P261 Avoid breathing mist. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear eye protection/ face protection.

#### Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

# Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

## Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

### Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
acetone	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	>= 50 - < 70
isobutane	75-28-5	Flam. Gas 1; H220	>= 20 - < 30
propane	74-98-6	Flam. Gas 1; H220	>= 10 - < 20

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

Revision Date 03/14/2024 Print Date 03/16/2024

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

irritant effects

Respiratory disorder Excessive lachrymation

Loss of balance

Vertigo

Causes serious eye irritation. May cause drowsiness or dizziness.

Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Dry powder Foam

Carbon dioxide (CO2)

Unsuitable extinguishing me- :

dia

Water

High volume water jet

Further information : Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Revision Date 03/14/2024 Print Date 03/16/2024

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages can-

not be contained.

#### SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic dis-

charges.

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the appli-

cation area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 122 °F. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in original container. Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : Explosives

Poisonous gases Poisonous liquids Radioactive Substances

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Revision Date 03/14/2024

Print Date 03/16/2024

Components	CAS-No.	Value type (Form of ex- posure)	Control parame- ters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
2 27		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
isobutane	75-28-5	STEL	1,000 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures

Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection Chemical-resistant, impervious gloves complying with an ap-

> proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Revision Date 03/14/2024

Print Date 03/16/2024

Hygiene measures Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove respiratory and skin/eye protection only after vapors

have been cleared from the area.

Remove contaminated clothing and protective equipment be-

fore entering eating areas.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Chemicals under pressure

Color colorless

Odor acetone-like

Odor Threshold : No data available

pΗ : ca. 5 - 6 (68 °F / 20 °C)

Concentration: 39.5 %

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

Flash point Not applicable

Evaporation rate : No data available

Flammability (solid, gas) Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

flammability limit

Vapor pressure : 8300 hpa

Relative vapor density No data available

: ca. 0.65 g/cm3 (73 °F / 23 °C) Density

Solubility(ies)

: No data available Water solubility

Solubility in other solvents No data available

Partition coefficient: n-oc-

tanol/water

No data available

Revision Date 03/14/2024 Print Date 03/16/2024

Autoignition temperature : > 464 °F / > 240 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 0.32 mPa.s (68 °F / 20 °C)

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

#### SECTION 11. TOXICOLOGICAL INFORMATION

Not classified due to lack of data.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Revision Date 03/14/2024

Print Date 03/16/2024

### Carcinogenicity

Not classified due to lack of data. IARC Not applicable

OSHA Not applicable

NTP Not applicable

## Reproductive toxicity

Not classified due to lack of data.

## STOT-single exposure

May cause drowsiness or dizziness.

### STOT-repeated exposure

Not classified due to lack of data.

### Aspiration toxicity

Not classified due to lack of data.

## SECTION 12. ECOLOGICAL INFORMATION

## Ecotoxicity

#### Components:

#### acetone:

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 530

mg/l

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

## Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its container in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Revision Date 03/14/2024

Print Date 03/16/2024

### Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

### Components:

# propane:

20-year global warming potential: 0.072 100-year global warming potential: 0.02 500-year global warming potential: 0.006

Atmospheric lifetime: 0.036 yr Radiative efficiency: 0 Wm2ppb

Further information: Miscellaneous compounds

#### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional lo-

cal authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

### SECTION 14. TRANSPORT INFORMATION

# International Regulations

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : Flammable Gas

Packing instruction (cargo : 203

aircraft)

Packing instruction (passen- : 203

ger aircraft)

IMDG-Code

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

Revision Date 03/14/2024 Print Date 03/16/2024

Remarks : Transport according to chapter 3.4 (LQ) possible

Domestic regulation

49 CFR

UN/ID/NA number : UN 1950 Proper shipping name : Aerosols Class : 2.1

Packing group : Not assigned by regulation

Labels : FLAMMABLE GAS

ERG Code : 126 Marine pollutant : no

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as ac-

tive on the TSCA Inventory or are in compliance with a TSCA

Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)
acetone	67-64-1	5000

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

Revision Date 03/14/2024

Print Date 03/16/2024

### California Prop. 65



WARNING: This product can expose you to chemicals including benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit OSHA P0 / TWA : 8-hour time weighted average OSHA P0 / STEL : Short-term exposure limit OSHA Z-1 / TWA : 8-hour time weighted average

## Notes to Reader

The data contained herein are furnished for information only and are believed to be reliable. However, Todol Products (hereafter Todol) does not assume responsibility for any results obtained by persons over whose methods Todol has no control. It is the user's responsibility to determine the suitability of Todol's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Todol specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Todol's products. Todol further disclaims any liability for consequential or incidental damages of any kind, including lost profits. This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Todol for additional assistance.

Revision Date 03/14/2024

100000030189 US / Z8